



Sakshi Chem
Sciences Pvt. Ltd.



2nd Floor, Vishal Furniture, Opp Police Station Sitabuldi, Nagpur – 440012., Ph. : 0712- 6617716, (M) 9422146423
Email - enquiry@sakshichemsciences.com, Website : . www.sakshichemsciences.com

ADDAGE MAXCARE WALL PUTTY

Description

Addage Wall Putty is white cement based putty. Better for interior & exterior walls. As white cement-based wall putty, it binds strongly with the base plaster, even if the surface is damp, and forms a protective base. It fills up the fine pores in the walls and ceiling, giving you a smooth and dry surface for painting on. With an effective protection against flaking, you are assured of a good looking home for years to come.

Features / Advantages.

- White cement based skim coat.
- Water resistant smooth surface for paint application.
- Excellent adhesion.
- No peel off due to seepage.
- Durability of paint increases, excellent finish, less consumption of paint.
- No primer required.
- No curing required.

Areas of application

- Plastered surface.
- Inner and Outer wall

Surface Preparation and Application

- The surface must be free from dust, coatings, loose particles, fungus, moss, oils, paints, bitumen, greases and mould release agents, etc.
- The surface should ideally be pre-wetted before applying Wall Putty. It helps in providing a strong bond with the substrate.
- Apply two coats (Max 1.5 mm total thickness for both the coats) of Addage Wall Putty on the plastered surface.

Coverage

- Addage Wall Putty covers more surface area exceeding 9-10 Sq. ft. /kg. In 2 coats on a new plastered wall.